

## TECHNICAL DATA SHEET

LFX IP20 / Xenon

VERSION - 16.03.2016


### STANDARD LUMINAIRE

Reference	LFX			
Protection Class	IP20			
Lighting Source	Xenon			
Connector	Rigid Loop on B'Light conductor 16mm <sup>2</sup>			
Dimensions	13 x 21mm			
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm			
Length on measure	on request up to 3000mm			
Nb Lighting Unit	18 bulbs/m			
Voltage	24V			
Power	3W	5W	8.5W	10W
	54 W/m	90 W/m	153 W/m	180 W/m

### APPLICATION: cornices, handrails, stairs, shelves



#### LFX / XENON - Rigid Loop




### FINISH

#### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Polished Aluminium Old Gold Aspect



#### LFX + FCP-S



### ON REQUEST

Fixation	BFA (Width: +12mm) FCP-S (Width: +2mm / Ht: +3mm)
Connecting Cable	COS3 - COS4 - COS4a
Connecting Plug	AF / AMS
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LFX + BFA




### LIGHTING SOURCE

Lighting Source	Xenon Long Life			
Glass	Clear or Frosted			
Power	3W	5W	8.5W	10W
Voltage	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°
Color Temperature	2300K	2400K	2600K	2500K
Light Output lm/unit	12.6lm	40lm	95lm	90lm
Lifetime	20'000h	20'000h	10'000h	20'000h


### ON REQUEST : Connecting Cable

#### COS3 Power Connector



2x1m conductors of 2.5mm<sup>2</sup>

#### COS4 Linear bridging



2x8cm conductors of 2.5mm<sup>2</sup>

#### COS4a Corner bridging



1x8cm conductors of 2.5mm<sup>2</sup>  
1x11cm conductors of 2.5mm<sup>2</sup>

### CERTIFICAT



### ON REQUEST : Connecting plug AF/AMS

