

## TECHNICAL DATA SHEET

### LU4CSAL IP20 / Aga-Led® Type A

VERSION - 06.01.2017

#### STANDARD LUMINAIRE

Reference	LU4CSAL
Protection Class	IP20
Lighting Source	Aga-Led® Type A
Connector	Festoon on B'Light conductor 16mm <sup>2</sup>
Dimensions	29 x 32mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	18 LED/m
Voltage	24V
Power	18 W/m
Connecting Cable	1m standard cable 2x1.5mm <sup>2</sup>

#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

#### ON REQUEST

Fixation	FCU (Width: +4mm)
End Caps	EU4
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LIGHTING SOURCE

Lighting Source	Aga-Led® Type A
Ref	A10
Voltage	24V
Power	1W
Beam Angle	15°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +55°C
Option	AGC: Anti Glare Optic



#### Color Temperature & Luminous Flux / Unit

<b>CCT</b>	<b>2800K</b>	<b>4000K</b>
<b>Luminous Flux/Unit</b>	<b>40 lm</b>	<b>45 lm</b>


#### CERTIFICAT




#### APPLICATION: Cornices, Windows, Balustrades



#### LU4CSAL - AGA-LED® TYPE A





#### ON REQUEST: LU4CSAL Fixation FCU



#### ON REQUEST: LU4CSAL Cover

##### VRC (or VRM)

##### VSC (or VSM)



#### ON REQUEST: LU4CSAL End Caps

##### EU4

##### EU4C



#### ON REQUEST : Connecting plug AF/AMS

