

TECHNICAL DATA SHEET

TLFALC IP20 / Aga-Led® Type B

VERSION - 02.09.0215


STANDARD LUMINAIRE

Reference	TLFALC
Protection Class	IP20
Lighting Source	Aga-Led® Type B
Connector	4 Positions on B'Light conductor 16mm ²
Dimensions	26 x 23mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	36 LED/m
Voltage	24V
Power	43.2 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

APPLICATION: cornices, handrails, stairs, shelves



TLFALC / AGA-LED® TYPE B - 4 Positions



FINISH


Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling
	Powder Coating RAL
	Color Anodising
	Polished Aluminium Chrome or Gold Aspect

ON REQUEST

Fixation	TFCP (Width: +3mm / Ht: +0.2mm)
	TFCP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX
	Ask technical departement for more information

TLFALC + FCP-S



LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2				
Ref	B2	B3	B4	B6	
Voltage	24V	24V	24V	24V	
Power	1.2W	0.96W	1.2W	1.2W	
Beam Angle	120°	120°	120°	120°	
CRI	80	80	80	80	
Color Temperature	lm/Unit				
	2000K	40 ~ 68	40 ~ 82	46 ~ 78	70 ~ 118
	2400K	48 ~ 81	58 ~ 97	55 ~ 93	83 ~ 140
	2800K	68 ~ 114	82 ~ 137	66 ~ 111	99 ~ 166
	4000K	68 ~ 114	82 ~ 137	66 ~ 111	99 ~ 166
Lifetime / L70 at 25°	50'000h / 36'000h				
Working T°	-20°C to +45°C				
Environmental protection	Modified acrylate resin				

ON REQUEST

Connecting plug AF/AMS



CERTIFICAT



AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
E - mail: info@aaabekov.com



AGABEKOV SA Bureau d'etudes 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
Internet: www.aaabekov.com

